




- 附注:
- 1.未注圆角为R0.05-0.2mm;
 - 2.最大毛边允许0.05mm;
 - 3.端子平面度: 0.1mm Max;
 - 4.产品符合RoHS环保要求;
 - 5.引脚电镀要求:
 - A.镍层厚度: 1.27um;
 - B.锡层厚度: 5.0um.
 - 6.引脚切断面须镀锡。

Code No.: FAY 01019

REMARK:		REV.	REVISIONS REC.	DATE:
1.		1.		
2.		2.		
DRAWN BY	Yuing.yu	TOLERANCES		
CHECKED BY	Yong.zhan	ANGLE:	MODEL NAME:	
APPROVED BY	Xueliang.zhan	0<L<4 ±0.10	±1°	ERI-7.5(4+4P)-1S
		4<L<16 ±0.20	UNIT:	BOBBIN MATERIAL:
		16<L<63 ±0.30	MM	PM9630
		Pin pitch: ±0.2	SCALE:	UL REC.
		Wall thickness: ±0.15	2:1	UL 94V-0
 天长市富安电子有限公司 TIAN CHANG FUAN ELECTRONIC CO.,LTD TEL:+86-550-7814888 FAX:+86-550-7831133 Http: www.fuantronics.net			PIN MATERIAL:	REV.
			C5191	0
		DRAWING NO:	SMD-ERI-7.5	DATE:
				2016.08.10